

2265+/2280+/LA650+/LA800+ SERIAL MATRIX PRINTERS



On board ethernet models available

**Ethernet hardware/software located
on main logic board**

Ribbon motion detection detects ribbon jams

PCL emulation model available

Automatic paper width detection

Up to 9-part forms

LAN IPDS version available

SPEED TO TACKLE ANY INDUSTRY APPLICATIONS

TOP SPEEDS UP TO 1,000 CPS

At top speeds up to 1,000 cps the 2265+ and 2280+ keep pace with the bustling, demanding world where printing is time sensitive and critical. Engineered for printing under adverse conditions, these devices produce multi-part invoices, shipping documents or bar code labels at a rate of up to 50,000 pages per month.

AFFORDABLE UPGRADES

For the most flexible paper handling, the 2280+ may be optionally configured with three input tractors (two front and one rear), while the 2265+ can be configured with two front tractors. Straight paper path on the front tractors of the 2265+ and 2280+ result in jam-free operation and flawless 24-wire impressions on up to 6-part forms. The 2265+ and 2280+ offers fully automated gap adjustment, paper parking, and loading.

MARKETS AND APPLICATIONS

Federal, State and Local Government:

Print tax forms, payroll checks, expense reports, inventory reports, invoices.

Manufacturing, Transportation and Distribution:

Print pick lists, shipping labels and freight bills.

Healthcare:

Handle a wide variety of media including bar code labels for patient charts, prescription labels, pre-printed forms for billing departments.

2265+/2280+/LA650+/LA800+ SERIAL MATRIX PRINTERS

Available Configuration.....**2265+**: Available in 10 configurations
2280+: Available in 7 configurations

Print Speed	2265+/LA650+ : At 10, 12, 15 cpi: high speed draft 650, 720, 900; draft 600, 720, 900, NLQ 200, 240, 300, LQ 100, 120, 150 2280+/LA800+ : At 10, 12, 15 cpi: high speed draft 800, 800, 1000; draft 667, 800, 1000; NLQ 222, 267, 333; LQ 111,133,167	Paper Weight	60 to 120 gm2 continuous forms; 60 to 90 gm2 cut sheet
Print Method	Serial impact	Paper Size	Length: 3" min, 22" max; Width: 3" min, 16.5" max
Resolution	360 x 360 dpi	Printable Area	Up to 13.6" width
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (emulation dependent)	Physical Weight	45.6 lbs.
Line Density	2, 3, 4, 6, 8, 12 lpi	Physical Size	24.5" x 11" x 17" (623mm x 280mm x 432mm)
Printhead Life	500 million characters (draft 12 x 12)	Power Voltage	AC 230V and 120V (selectable)
Printhead Type	24 wire	Power Frequency	50/60Hz
Memory	128kB	Power Consumption	2265+/LA650+ : 60 watts operating, max 14 watts stand-by 2280+/LA800+ : 70 watts operating, max 15 watts stand-by
Standard Connectivity	Bi-directional Centronics parallel	Compliance	Ozone-free. RoHS, Microsoft, ISO-compliant, Meditech approved
Optional Connectivity	RS232 serial, Ethernet, Ethernet IPDS, Tx/Cx, Tx/Cx IPDS	Workload	2265+/LA650+ : Up to 40,000 pages per month 2280+/LA800+ : Up to 50,000 pages per month
Standard Emulation	2265+/2280+ : IBM Proprinter XL24e, Epson LQ-2550, Epson LQ-2170 (ESC P/2), MTPL LA650+/LA800+ : DEC ANSI PPL2, IBM Proprinter XL24e, Epson LQ-2550, Epson LQ-2170 (ESC P/2)	Reliability MTBF	10,000 hours @ 25% duty cycle
Optional Emulation	PCL3	Drivers	Windows 2000, XP, Vista, Windows 7, Server 2003, Server 2008; SAP
Fonts	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP fonts. Intelligent Mail Barcode	Temperature	Operating +10°C to +35°C; storage +5°C to +45°C
Consumables	20 million characters	Humidity	Operating 15% to 75%; Storage 5% to 95% (relative humidity)
STD Paper Handling	Front insertion, push tractor with paper parking and AGA; 2nd rear push tractor (2280-2T only)	Acoustic	2265+/LA650+ : 55 dBA (ISO 7779) 2280+/LA800+ : 57 dBA (ISO 7779)
Optional Paper Handling	Additional front push tractor, automatic dual-bin sheet feeder (190 sheets per bin), face down output, paper cutter	Warranty	For warranty information go to www.tallygenicom.com
Number of Copies	2265+/LA650+ : Front: original + 6 (7-part forms); with high impact print head model – Back: original +8 (9 part forms) 2280+/LA800+ : Front: original + 5 (6-part forms); Back: original + 1 (2-part forms)	Option 1	Second front push tractor, paper cutter, dual bin sheet feeder
Paper Type	Continuous paper, cut sheets (optional feeder)	Option 2	Internal Ethernet, RS232 serial
		Option 3	Printer stand, paper basket, pedestal cabinet, cable cover, castors

For further information about our products and services, please visit our website at:
www.tallygenicom.com

Southern Europe, Iberia & Middle East and Africa – PRINTRONIX France Sarl
 13 Rue Salomon de Rothschild, 92150 Suresnes, France
 Tel: +33 (0) 1 46 25 19 00

Northern Europe – PRINTRONIX UK Ltd
 Millars Brook, Unit 3, Molly Millars Lane, Wokingham, Berkshire
 Tel: +44 (0) 118 977 1000

For sales enquiries, please email:
emeasales@printronix.com

Central & Eastern Europe –
 PRINTRONIX Deutschland GmbH
 Goethering 56, D-63067 Offenbach, Germany
 Tel: +49 (0) 69 82 97 06 0

Middle East and Africa
 Jebel Ali Free Zone, PO Box 262746, South Zone, Dubai
 Tel: +971 (4) 8137866

For technical support, please email:
emeasupport@printronix.com

Russia and C.I.S. –
 PRINTRONIX Inc, Moscow Representative Office
 Balakirevsky per., 19, office 106, 105082 Moscow, Russian Federation
 Tel: +7 (495) 737 9387

Customer Support Centre EMEA –
 PRINTRONIX Netherlands BV
 Nieuweweg 283, P.O. Box 163, NL-6600 AD Wijchen, Netherlands
 Tel: +31 (0) 24 64 89 489

