

9045N MONOCHROME LASER PRINTER



Less than 8 seconds first page output time

1200 x 1200 dpi at up to 45 ppm

Powerful 533 MHz RISC processor

Intellifilter™ for compatibility with legacy print data streams

Intelliprint™ controller

Adobe PostScript 3, PCL6, PCL5e

Optional duplex printing

Duty cycle of 200,000 images per month

UNMATCHED FUSION OF PERFORMANCE AND PRODUCTIVITY

POWERFUL

At less than 8 seconds to print a letter size page, the 9045N has a powerful print engine with its 533MHz processor. Combine this with TallyGenicom's market leading Intelliprint controller technology and enough memory as standard, and you have the most powerful workgroup printer available today. The 9045N is ideally suited for heavy workload printing applications, where short print time is critical.

PRODUCTIVE

Capable of up to 200,000 pages per month and 45 pages per minute, the 9045N will more than meet the demands of a busy office. The 9045N can be configured with an impressive list of paper handling features including multiple bins and a duplexer.

INTELLIGENT MIGRATION

The on-board Intellifilter enables true migration from other print technologies such as line printer or serial dot matrix.

SECURE PRINTING

Add the hard drive option and secure printing is enabled. Just type your private password in the printer and collect your print job. In addition, job accounting, a job library, collation and the ability to store forms, fonts and logos become possible with the hard disk option.

9045N MONOCHROME LASER PRINTER

Available Configuration.....**9045N**: Available in 4 configurations

Print Speed	45 ppm letter, 43 ppm A4	Power Voltage	10-127 VAC, 50/60 Hz; current: 11 amps
Print Method	Electro-photographic semiconductor laser with Intelliprint controller	Power Consumption	Less than 30 watts standby, less than 850 watts printing (average). Typical Energy Consumption (TEC): 6.69 kWh/week or less for ENERGY STAR® qualified models
Processor	MIPS R7035 533 MHz	Compliance	ENERGY STAR qualified, for 120V UL60950-1; CSA C22.2 No. 60950-1-03; FDA 21 CFR Chapter 1, Subchapter J, Section 1010, 1040 Laser Safety, NOM, FCC Part 15 Class B; For 220V: IEC 60950-1 and 60825-1 Class 1, RoHS, Microsoft, ISO-compliant, Meditech Approved
Resolution	600 x 600 dpi and 1200 x 1200 dpi	Workload	Up to 200,000 pages per month
Time To 1st Page	Less than 8 Seconds	Forms Software	Intellifilter and TG Forms compatible
Memory	128MB expandable to 640MB; optional 40GB hard drive	Drivers	Windows 2000, XP, Vista, Windows 7, Server 2003, Server 2008 Postscript 3 and PCL Drivers; Mac OSX; UNIX and LINUX Compatibility
Standard Connectivity	Standard 10/100Base-T Ethernet; TCP/IP, EtherTalk, Bonjour; EEE 1284 parallel; Hi-Speed USB 2.0 480 Mb/s auto interface connectivity switching; RS232	Temperature	Operating 50°F to 90°F (10°C to 32°C)
Standard Emulation	PostScript 3; PCL6, PCL5c, PCL5e	Humidity	Operating: 15% to 85% non-condensing
Print Monitor	SNMP, Printer MIB, e-mail status, and Web-based status and control, TGNetAdmin	Acoustic	Printing - 56.1 dBA; Standby - 28 dBA
Fonts	136 Adobe PostScript fonts; 86 Type 1 PCL	Warranty	For warranty information go to www.tallygenicom.com
Consumables	Low yield cartridge: 13,000 letter pages, high yield: 22,000 letter pages (at 5% coverage for both)	Option 1	Add-on tray - 550 sheet feeder; duplexer; offset catch tray
Maintenance	200K letter/A4	Option 2	256MB, 512MB DIMM
STD Paper Handling	550-sheet tray; 150-sheet tray	Option 3	Hard disk
Optional Paper Handling	550-sheet feeder tray (up to 2 additional)	Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used. Toner saver mode provides up to 40% savings.
Duplexing	Optional		
Paper Type	Sheet paper, transparencies, bond, labels, envelopes, and thick media		
Paper Weight	16 to 58 lbs in simplex and duplex modes		
Paper Size	Letter, executive, legal, folio, A4, A5, A6, B5, statement; envelopes: Com10, Monarch, DL, C5; custom sizes: 3.88 to 8.50 W by 5.83 to 14.00 L (tray 1 and 2 only); Officio (8.5" x 13.38" - supported as a custom size in tray #1 or #2)		
Paper Output	500-sheet face-down top output; optional cassette: 500-sheet offset catch tray		
Physical Weight	45 lbs. (20.6 kg)		
Physical Size	15.9" x 16.6" x 18.3" (404 x 422 x 465 mm)		

For further information about our products and services, please visit our website at:
www.tallygenicom.com

Southern Europe, Iberia & Middle East and Africa – PRINTRONIX France Sarl
13 Rue Salomon de Rothschild, 92150 Suresnes, France
Tel: +33 (0) 1 46 25 19 00

Northern Europe – PRINTRONIX UK Ltd
Millars Brook, Unit 3, Molly Millars Lane, Wokingham, Berkshire
Tel: +44 (0) 118 977 1000

For sales enquiries, please email:
emeasales@printronix.com

Central & Eastern Europe – PRINTRONIX Deutschland GmbH
Goethering 56, D-63067 Offenbach, Germany
Tel: +49 (0) 69 82 97 06 0

Middle East and Africa
Jebel Ali Free Zone, PO Box 262746, South Zone, Dubai
Tel: +971 (4) 8137866

For technical support, please email:
emeasupport@printronix.com

Russia and C.I.S. – PRINTRONIX Inc, Moscow Representative Office
Balakirevsky per., 19, office 106, 105082 Moscow, Russian Federation
Tel: +7 (495) 737 9387

Customer Support Centre EMEA – PRINTRONIX Netherlands BV
Nieuweweg 283, P.O. Box 163, NL-6600 AD Wijchen, Netherlands
Tel: +31 (0) 24 64 89 489



© 2010 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint, Intellipress and Printronix are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice. TG200UK 5/10

14600 Myford Road, Irvine, CA 92606
800-665-6210 • www.tallygenicom.com

PRINTRONIX